



MASTER TL-D HF Super 80

MASTER TL-D HF Super 80 16W/840 1SL

The MASTER TL-D HF Super 80 lamp offers more lumens per watt and better color rendering than TL-D standard colors. Furthermore, it has a lower mercury content. The lamp is designed to be operated on special high-frequency electronic ballasts. It is not for general use.

Product data

• General Characteristics

System Description	High Frequency [High Frequency]
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Bulb	T8 [26 mm]
Life to 10% fail	17000 hr
Preheat EL,3h	
Life to 10% fail	10000 hr
Nonpreh EL,3h	
Life to 50% fail	20000 hr
Preheat EL,3h	
Life to 50% fail	12000 hr
Nonpreh EL,3h	
LSF HF Preheat	99 %
2000h Rated,3h	
LSF HF Preheat	99 %
4000h Rated,3h	
LSF HF Preheat	99 %
6000h Rated,3h	
LSF HF Preheat	99 %
8000h Rated,3h	
LSF HF Preheat	99 %
12000h Rated,3h	
LSF HF Preheat	95 %
16000h Rated,3h	
LSF HF Preheat	50 %
20000h Rated,3h	

• Light Technical Characteristics

Color Code	840 [CCT of 4000K]
Color Rendering Index	85 Ra8
Color Designation (text)	Cool White
Color Temperature	4000 K
Luminous Flux EL	1400 Lm
25°C, Rated	

Luminous Flux EL	1400 Lm
25°C, Nominal	
Lum Efficacy Rated	87.5 Lm/W
HF 25°C	
Luminance Average	1.04 cd/cm ²
EL	
LLMF HF 2000h	96 %
Rated	
LLMF HF 4000h	95 %
Rated	
LLMF HF 6000h	94 %
Rated	
LLMF HF 8000h	93 %
Rated	
LLMF HF 12000h	92 %
Rated	
LLMF HF 16000h	91 %
Rated	
LLMF HF 20000h	90 %
Rated	
Design Temperature	25 C
Chromaticity Coordinate X	384 -
Chromaticity Coordinate Y	381 -

• Electrical Characteristics

Lamp Wattage	16 W
Lamp Wattage EL	16.0 W
25°C, Rated	
Lamp Wattage EL	16 W
25°C, Nominal	
Lamp Voltage EL	64 V
25°C	
Lamp Current EL	0.255 A
25°C	



MASTER TL-D HF Super 80

Dimmable Yes

Overall Length C 604 (max) mm
Diameter D 28 (max) mm

• Environmental Characteristics

Energy Efficiency Label (EEL) A
Mercury (Hg) Content 2.0 mg
Energy consumption kWh/1000h 20 kWh

• Product Data

Order code 927924084023
Full product code 927924084023
Full product name MASTER TL-D HF Super 80 16W/840 1SL
Order product name MASTER TL-D HF Super 80 16W/840 1SL/25
Pieces per pack 1
Packing configuration 25
Packs per outerbox 25
Bar code on pack - EAN1 8711500631473
Bar code on outerbox - EAN3 8711500631480
Logistic code(s) - 12NC 927924084023
ILCOS code FDH-16/40/1B-L/P-G13-26/600
Net weight per piece 78.400 gr

• Measuring Conditions

Calibration Current 0.255 A
HF Generator Rated Voltage 128 V
Resistor 250 ohm

• Product Dimensions

Base Face to Base 589.8 (max) mm
Face A
Insertion Length B 594.5 (min), 596.9 (max) mm



Warnings and Safety

- Special electronic gear must be used

Dimensional drawing



MASTER TL-D HF Super 80 16W/840 1SL

Product	A (Max)	B (Min)	B (Max)	C (Max)	D (Max)
TL-D HF 16W/840	589.8	594.5	596.9	604	28



G13

Photometric data



© 2015 Koninklijke Philips N.V. (Royal Philips)
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2015, February 23
data subject to change